

BALE BUGGY

The Giltrap Bale Buggy is a rear feeding, single bale small tractor or ute drawn feeder. It is designed to handle all types of round bales. The Buggy is ground driven and is designed to feed out baleage minimising pasture damage because the unit does not require a tractor.



KEY FEATURES

- Handles all types of round baleage
- Feeds out to the rear, with even feed flow so that baleage doesn't get caught up in the chains
- Feed chains are geared 3 x slower than ground speed, so the feed mat is not continuous, and reduces the torque load on the ground drive wheel to reduce slippage in muddy conditions
- The bale weight is forced forward while feeding which keeps load on the drawbar for traction on the towing vehicle, and reduces the risk of the bale falling off the back going up hills
- Easy to use bale loading system
- No tractor hydraulics required

To view the full list of features and optional extras, and find your local dealer, visit www.giltrapag.co.nz





Length (mm)	3400
Width (mm)	2150
Height (mm)	1520
Weight (unladen) (kg)	433
Max./ bale size (round)	1.80m (dia) x 1.35m
Feed chains	8mm high tensile link

FEATURES



Release the locking latch to tip the bale buggy backwards to touch the ground.



Use the winch to load the bale into the feed chamber and bring the bale buggy back to the upright position.



Engage the ground wheel drive and you are ready to go feeding.